




TD HANDY-SCAN^{RX} - Multi-Function Ultrasonic Inspection Systems



Features

- Highly Portable
- Sunlight Readable Screen
- Extensive Analysis Tools
- Powerful Reporting Functions
- Removable Battery
- 2 Axis Encoder; Video tracking
- Import setups from ESBeamTool[®]
- x 8 Conventional Channels
- 32/64 Phased Array
- Simultaneous PA, ToFD and/or PE data collection
- 128GB SSD storage

Techniques

- Phased Array
- ToFD
- Pulse Echo
- Corrosion Mapping
- Weld Zone Discrimination

Applications

- Pressure Vessel Welds
- Pipeline Welds
- Corrosion Surveys
- Turbine Disks & Blades
- Complex Geometries
- Forgings & Castings
- Aircraft Components
- Hydrogen Damage Surveys

Software

- Phased Array/Pulse Echo
- ToFD
- Strip-Scan (AUT)
- Long Range (Creep Wave & Corrosion Mapping)
- TD Super-View
- ESBeamTool[®] included

E&OE - All specifications are subject to change. It is advisable to check all information provided.



TD Handy-ScanRX Hardware Specification

Hardware

System Options		
64 Elements (D Type 78 way)	32 Active	8 Conventional (Lemo 00)
General		
Number Of Focal Laws	1700 max	
Dynamic Depth Focusing	Yes	
Digitisation		
A/D Sampling Frequency	Phased Array = 8Bit & 14Bit @ 100MHz Conventional = 8Bit & 14Bit @ 100MHz	
System Bandwidth(-3dB)	Phased Array = 0.75MHz to 25MHz Conventional = 0.75MHz to 25MHz	
Max Pulse Repetition Frequency	Variable up to 5KHz	
Pulser		
Number Of Pulsers	64	
Number Of Active Pulsers	1 to 32	
Pulser Delays	0µs to 20µs in 2.5ns steps	
Output Impedance	6 Ohms	
HT Pulse Shape	Square wave	
HT Pulse Voltage	Phased Array = 5 to 190V in 1V Steps Conventional = 5 to 190V in 1V Steps	
HT Pulse Width Range	20ns to 500ns in 2.5ns steps	
Rise/fall time	< 5ns	
Receiver		
Number Of Receivers	64	
Number Of Active Receivers	1 to 32	
Receiver Delays	0µs to 20µs in 1ns steps	
Gain Range	P/E=0 to 90dB in 0.1dB steps, P/A=0 to 72dB in 0.1dB steps	
Input Noise Level	2.5nV/(Hz) ½ across full system bandwidth	
Input Impedance	50 Ohms	
Dynamic Depth Focusing		
Operation	Dynamically optimises receive focus delays	
Range Of Operation	User specified depth/range in mm or µs	
Performance	100MHz real-time	
Receiver DAC Curves		
Number Of Curves	1 to 8	
Rate Of Gain Change	Up to 40dB/µs	
A-Scan Digitizing		
A-Scan Points Per Channel	8000 samples per channel	
Number Of Gates Per Channel	3 overlapping hardware Gates	
Gate Start/Width	User definable in 40ns steps	
Gate Reference Points	Transmit Pulse or Material Interface Echo	
Storage Modes Per Gate	A-Scans, Peak Depth and Amplitude, both	

Software

General Features

- Simultaneous Phased Array, ToFD & Pulse Echo data collection
- Operator definable weld geometry overlays
- Real-time A, B, C and D-Scan images, with user defined display modes
- Internal report generation including interactive print-preview & user-definable report fields
- Full cursor analysis indicating peak depth, amplitude and x,y position
- Export Bitmap images to any Windows application
- 8 or 14 bit Data collection (Phased array/Pulse Echo/ToFD)
- Import ESBeamTool® setups

Phased Array

- User configurable control of beam angle, focal distance and spot size
- Fixed-angle electronic or sectorial scans
- Dynamic Depth Focusing (DDF) provides a user-definable focal range
- 2000 Focal laws
- Supports linear probe/wedge geometry
- Normalisation of amplitude across sectorial scan angles or fixed angle focal laws
- Beam Apodization
- Skip Correction provides correct depth/range relationship for multiple legs

Signal Averaging

Number Of Channels All (128 software channels)
Averaging Rates Real-time averaging 2 - 256, user definable

Peak Processing

Peak Storage Modes All Peaks, First Peak, Largest Peak/s, Loss of Signal, Between
Threshold Setup 5 to 100% in 1% steps per hardware Gate
Number Of Peaks Per Gate 16 max

Scanner Interface Ports

Input Type Encoder, Potentiometer, Video Camera
Number Of Axis 2 axis, TTL compatible
Encoder Interface TTL compatible, 5V @ 1A, 12V @ 0.4A
Potentiometer Interface 0 to 2.5V, sampled at 100Hz
Video Input 1Vpp Composite

PC (Internal)

Operating System Windows® 7
3rd Party Software AVG Antivirus®
ESBeamTool® (Eclipse Scientific)
Processor Intel Atom N270
Memory 2GB
Display Colour TFT (Industrial type) 8.4"
TFT Display Resolution 800 x 600 - Sunlight Readable Screen
Storage 128GB SSD
Ports 2 x USB, 1 x 10/100 Ethernet, 1 x Video

Size, Weight and Environmental

Unit Dimensions 270 x 300 x 110mm
Weight 5Kg
Temperature 0°C to 40°C operating, -25°C to 85°C storage

Battery Capability

Operating Time 4 Hours (approx)
DC Input 19V
AC Input 90 to 260VAC @ 40Hz to 60Hz

Pulse Echo

- Independent control of transmit and receive parameters
- C-scan with end views for corrosion mapping
- Trigger reference modes including Interface Echo or Tx Pulse
- Multiple peak data storage modes, including full/selective A-Scan storage

ToFD

- Perform multi-channel TOFD and Pulse Echo inspections simultaneously
- Full suite of image analysis tools for defect/crack sizing
- Real-time multi-channel averaging significantly improves signal quality
- Linearization, Straightening, Synthetic-Aperture-Focusing-Technique (SAFT)
- File utilities include file join, split, reverse, save partial, output data to text file etc.

Weld Zone Discrimination

- Combined TOFD, Time/Amplitude view, Map view, Couplant Check & Go/No-Go in a single pass
- Inspection data displayed as strips indicating weld zones
- Integrated TOFD analysis
- Automated report generator

E&OE - All specifications are subject to change. It is advisable to check all information provided.